


Appendix G

Pine Street Cross Sections


Town of Pinedale

Transportation Master Plan







TYPE A




TYPE B



TYPE C



TYPE D



**TYPICAL DOUBLE
GUTTER (3' WIDE)**

"D" = 2'-6" UNLESS OTHERWISE
SPECIFIED IN THE PLANS

ALL CONCRETE CONTROL JOINTS SHALL
BE TOOLED UNLESS OTHERWISE
APPROVED BY ENGINEER.

CURB, GUTTER, AND SIDEWALK NOTES:

1. PROVIDE CLASS 4000 CONCRETE FOR ALL CURB, GUTTER AND SIDEWALK. PLACE AND CURE CONCRETE IN ACCORDANCE WITH SECTION 3310.
2. INSTALL $\frac{1}{2}$ " PREFORMED EXPANSION JOINT FILLER AGAINST ALL EXISTING CONCRETE EDGES AND IN CURB, GUTTER AND SIDEWALK AT A MAXIMUM OF 150' SPACING.
3. PROVIDE SIDEWALKS AND ADA ACCESSIBILITY AS SPECIFIED. IF LOCATIONS DO NOT FACILITATE THE PLANS PROVIDED, ALTERNATE SIDEWALK/RAMP LAYOUTS MAYBE UTILIZED PER WYOMING DEPARTMENT OF TRANSPORTATION (STANDARD PLANS 608), AS APPROVED BY THE ENGINEER.

**TYPICAL CURB AND GUTTER TYPE
NO SCALE**



ORIGINAL DRAWINGS PRODUCED BY WLC FOR THE TOWN OF PINEDALE. ANY MODIFICATION TO THE DRAWINGS WITHOUT PRIOR CONSENT FROM THE TOWN OF PINEDALE AND WLC IS PROHIBITED. ANY USER OF THIS INFORMATION WITHOUT PRIOR WRITTEN CONSENT AGREES TO WAIVE ALL CLAIMS AGAINST WLC ARISING FOR THE SERVICE PERFORMED BY WLC.

TRAVEL WAY WIDTHS (MINIMUM)			
DESIGN SPEED	CROSS SLOPE	ROAD WIDTH	1/2 WIDTH
20 mph	3%	28'	15'
30 mph	3%	36'	18'
40 mph	2%	40'	20'

NOTES:

ALL STREET CONSTRUCTION SHALL PROVIDE FOR THE FOLLOWING:


1. ADA PEDESTRIAN ACCESS (AT LEAST ONE SIDE).
2. ADEQUATE STORAGE FOR SNOW REMOVAL.
3. STORMWATER DRAINAGE CONVEYANCE TO A DESIGNATED LOCATION.
4. ROADWAY PROFILE GRADE MINIMUM IS 0.5% UNLESS APPROVED BY TOWN ENGINEER.



ROADWAY STANDARDS


ORIGINAL DRAWINGS PRODUCED BY WLC FOR THE TOWN OF PINEDALE. ANY MODIFICATION TO THE DRAWINGS WITHOUT PRIOR CONSENT FROM THE TOWN OF PINEDALE AND WLC IS PROHIBITED. ANY USER OF THIS INFORMATION WITHOUT PRIOR WRITTEN CONSENT AGREES TO WAIVE ALL CLAIMS AGAINST WLC ARISING FROM THE SERVICE PERFORMED BY WLC.






STREET WITH ATTACHED SIDEWALK (40' MIN R/W)

NO SCALE



STREET WITH DETACHED SIDEWALK (55' MIN R/W)

NO SCALE



STREET SECTION WITH SWALES (60' MIN R/W)

NO SCALE

ROADWAY STANDARDS

ORIGINAL DRAWINGS PRODUCED BY WLC FOR THE TOWN OF PINEDALE. ANY MODIFICATION TO THE DRAWINGS WITHOUT PRIOR CONSENT FROM THE TOWN OF PINEDALE AND WLC IS PROHIBITED. ANY USER OF THIS INFORMATION WITHOUT PRIOR WRITTEN CONSENT AGREES TO WAIVE ALL CLAIMS AGAINST WLC ARISING FROM THE SERVICE PERFORMED BY WLC.




DRAWING DATE:




TOWN OF PINEDALE

STANDARD DRAWING

"D" = 2'-6" UNLESS OTHERWISE SPECIFIED IN THE PLANS



TYPE "C" ROLLOVER CURB & GUTTER WITH SIDEWALK
NO SCALE





TYPE "A" HIGH BACK CURB & GUTTER WITH SIDEWALK
NO SCALE

NOTES:

1. SUBGRADE COMPACTION SHALL CONFORM TO SECTION 2210.
2. 3/4" EXPANSION JOINT MATERIAL SHALL BE PLACED AT PC, PT, CURB RETURNS AND STRAIGHT RUNS EVERY 150' MAXIMUM.
3. JOINTING SHALL COMPLY WITH SECTIONS 2528 AND 3251.
4. NO CURB AND GUTTER SHALL BE PLACED WITHOUT A FINAL FORM INSPECTION BY THE ENGINEER.
5. CURB AND GUTTER SHALL BE CLASS 4000 CONCRETE UNLESS OTHERWISE SPECIFIED.
6. CONTRACTION JOINTS SHALL BE CONSTRUCTED BY SCORING. SCORING TOOL SHALL LEAVE ROUNDED CORNERS AND PENETRATE TO A DEPTH $0.12 \times$ DEPTH OF CONCRETE.
7. DETACHED SIDEWALK MUST BE INSTALLED WITHIN 1' OF THE PROPERTY BOUNDARY.

TYPE A & TYPE C CURB AND GUTTER WITH SIDEWALK
NO SCALE

ORIGINAL DRAWINGS PRODUCED BY WLC FOR THE TOWN OF PINEDALE. ANY MODIFICATION TO THE DRAWINGS WITHOUT PRIOR CONSENT FROM THE TOWN OF PINEDALE AND WLC IS PROHIBITED. ANY USER OF THIS INFORMATION WITHOUT PRIOR WRITTEN CONSENT AGREES TO WAIVE ALL CLAIMS AGAINST WLC ARISING FOR THE SERVICE PERFORMED BY WLC.





* RAMP WIDTH SHALL BE 5FT EXCEPT WHERE ENGINEER DETERMINES THAT IT IS NOT FEASIBLE, THEN A WIDTH OF 3' MIN. SHALL BE USED.

ALL SIDEWALKS SHALL BE ADA ACCESSIBLE

TYPICAL STREET INTERSECTION DETAIL ATTACHED SIDEWALK

NO SCALE

ORIGINAL DRAWINGS PRODUCED BY WLC FOR THE TOWN OF PINEDALE. ANY MODIFICATION TO THE DRAWINGS WITHOUT PRIOR CONSENT FROM THE TOWN OF PINEDALE AND WLC IS PROHIBITED. ANY USER OF THIS INFORMATION WITHOUT PRIOR WRITTEN CONSENT AGREES TO WAIVE ALL CLAIMS AGAINST WLC ARISING FOR THE SERVICE PERFORMED BY WLC.




* RAMP WIDTH SHALL BE 5FT EXCEPT WHERE ENGINEER DETERMINES THAT IT IS NOT FEASIBLE, THEN A WIDTH OF 3' MIN. SHALL BE USED.

ALL SIDEWALKS SHALL BE ADA ACCESSIBLE


TYPICAL STREET INTERSECTION DETAIL DETACHED SIDEWALK

NO SCALE


ORIGINAL DRAWINGS PRODUCED BY WLC FOR THE TOWN OF PINEDALE. ANY MODIFICATION TO THE DRAWINGS WITHOUT PRIOR CONSENT FROM THE TOWN OF PINEDALE AND WLC IS PROHIBITED. ANY USER OF THIS INFORMATION WITHOUT PRIOR WRITTEN CONSENT AGREES TO WAIVE ALL CLAIMS AGAINST WLC ARISING FOR THE SERVICE PERFORMED BY WLC.



**TYPICAL DRIVEWAY
PLAN VIEW**
NO SCALE






TYPICAL DRIVEWAY CURB-CUT
NO SCALE



TYPICAL ADA RAMP CURB CUT
NO SCALE

DRIVEWAY AND CURB CUT DETAILS
NO SCALE

ORIGINAL DRAWINGS PRODUCED BY WLC FOR THE TOWN OF PINEDALE. ANY MODIFICATION TO THE DRAWINGS WITHOUT PRIOR CONSENT FROM THE TOWN OF PINEDALE AND WLC IS PROHIBITED. ANY USER OF THIS INFORMATION WITHOUT PRIOR WRITTEN CONSENT AGREES TO WAIVE ALL CLAIMS AGAINST WLC ARISING FOR THE SERVICE PERFORMED BY WLC.



*NOTES: DRIVEWAY SLOPES MUST BE BETWEEN 1%-4% UNLESS APPROVED BY ENGINEER

TYPICAL DRIVEWAY-STREET CONNECTIONS

NO SCALE

ORIGINAL DRAWINGS PRODUCED BY WLC FOR THE TOWN OF PINEDALE. ANY MODIFICATION TO THE DRAWINGS WITHOUT PRIOR CONSENT FROM THE TOWN OF PINEDALE AND WLC IS PROHIBITED. ANY USER OF THIS INFORMATION WITHOUT PRIOR WRITTEN CONSENT AGREES TO WAIVE ALL CLAIMS AGAINST WLC ARISING FOR THE SERVICE PERFORMED BY WLC.

